

IN THE CLAIMS

Please amend claims 3, 5, and 9-12 as follows.

1. (Original) A packet-switched communication apparatus which forwards packets pertaining to communication setup between two client terminals, one terminal being attached to a first network and the other terminal being attached to a second network, wherein said first network which carries packets by using a first protocol and said second network which carries packets by using a second protocol are connected via an address translator,

said packet-switched communication apparatus comprising:

mapping retaining means for retaining mappings between network-dependent parts of addresses which are used in said first network and address translators;

address translator selecting means for selecting one of said address translators, based on an address included in a received packet;

address obtaining means for obtaining a substitutive address to replace the address included in the received packet from the selected address translator; and

address replacement means for replacing the address included in the received packet by using the obtained substitutive address.

2. (Original) The packet-switched communication apparatus according to claim 1, wherein said first network and said second network run different protocols of a third layer, and

wherein said address to be replaced is included in a section which is a fourth layer or higher of the received packet.

3. (Currently Amended) The packet-switched communication apparatus according to claim 1 ~~or 2~~, wherein said mapping retaining means may retain a plurality of address translators mapped to one network-dependent part of an address included in the received packet, and

wherein said address obtaining means selects one of said plurality of address translators associated with an address included in the received packet and sends a request to the selected address translator to obtain said substitutive address.

4. (Original) The packet-switched communication apparatus according to claim 3, wherein, after said address obtaining means sends a request for said substitutive address to any address translator selected from said plurality of address translators, if said address obtaining means fails to obtain said substitutive address from the address translator,

said address obtaining means selects another address translator out of said plurality of address translators and sends a request for said substitutive address to said another address translator.

5. (Currently Amended) The packet-switched communication apparatus according to claim 3~~or 4~~, wherein said address obtaining means repeats the sending of the request for said substitutive address to the selected address translator until predetermined conditions are met.

6. (Original) The packet-switched communication apparatus according to claim 5, wherein said address obtaining means repeats the sending of the request for said substitutive address to the selected address translator until obtaining the substitutive address of need.

7. (Original) The packet-switched communication apparatus according to claim 5, wherein said address obtaining means repeats the sending of the request for said substitutive address to all the address translators mapped to the network-dependent part of said address.

8. (Original) The packet-switched communication apparatus according to claim 5, wherein said address obtaining means repeats the sending of said request by a preset number of times.

9. (Currently Amended) The packet-switched communication apparatus according to ~~any one of claims 1 through 8,~~

wherein said first network is an IPv6 network, and

wherein the network-dependent part of said address is a prefix value of an IPv6 address of a client terminal which is connected to said IPv6 network.

10. (Currently Amended) The packet-switched communication apparatus according to ~~any one of claims 1 through 9,~~

wherein said address replacement is intended to replace an address specified for a query for a name corresponding to the address of a client terminal for communication in accordance with a DNS protocol,

wherein, if said address is an IPv4 address, said address obtaining means obtains an IPv6 address as the substitutive address;

if said address is an IPv6 address, said address obtaining means obtains an IPv4 address as the substitutive address.

11. (Currently Amended) The packet-switched communication apparatus according to ~~any one of claims 1 through 9,~~ wherein, after said address obtaining means obtains

said substitutive address, the address or a string including the address included in the received packet is replaced by said substitutive address or a string including the substitutive address and the packet is forwarded to a predetermined destination.

12. (Currently Amended) The packet-switched communication apparatus according to ~~any one of claims 1 through 9~~, wherein, if said address obtaining means fails to obtain said substitutive address, the received packet is forwarded as is to the predetermined destination.

13. (Original) The packet-switched communication apparatus according to claim 1,

wherein said address translator selecting means select one of said address translators, based on a source address of the received packet, and

wherein said address obtaining means sends a request for a substitutive address to the selected address translator.

14. (Original) The packet-switched communication apparatus according to claim 10, wherein, upon receiving a name resolution request packet for a name corresponding to an IPv4 address, query data included in the received name resolution request packet is replaced by the obtained substitutive address and a name resolution request packet with

the replaced query data is transmitted to a DNS server, when a source IPv6 address of the received name resolution request packet is mapped to an ID of the name resolution request packet to transmit,

wherein said packet-switched communication apparatus further comprises packet ID retaining means for retaining a mapping between said source IPv6 address and said ID of the request packet, and

wherein, upon receiving a reply packet for notification of the name corresponding to the IPv6 address, said address obtaining means selects one of said address translators, based on the IPv6 address mapped to the ID of the reply packet, and sends a request for a substitutive IPv4 address to the selected address translator.

15. (Original) The packet-switched communication apparatus according to claim 10, wherein, upon receiving a name resolution request packet for a name corresponding to an IPv6 address, said address obtaining means selects one of said address translators, based on the IPv6 address corresponding to a string to be resolved to a name by the request included in the packet, and sends a request for a substitutive IPv4 address to the selected address translator.

16. (Original) The packet-switched communication apparatus according to claim 15, wherein, upon receiving a reply packet for notification of the name corresponding to the IPv4 address, said address obtaining means selects one of said address translators, based on the source IPv6 address of the packet, and sends a request for a substitutive IPv6 address to the selected address translator.

17. (Original) A communication method for forwarding packets pertaining to communication setup between two client terminals, one terminal being attached to a first network and the other terminal being attached to a second network, wherein said first network which uses IPv6 and said second network which uses IPv4 are connected via an address translator, said communication method to be applied in a packet-switched communication apparatus which is connected to said IPv6 network and retains mappings between IPv6 address prefixes and address translators, each being responsible for a specific range of the prefixes, comprising:

receiving a name resolution request packet on behalf of a DNS server;

upon receiving said name resolution request packet, selecting one of said address translators, based on an address included in the name resolution request packet, referring to

said mappings retained on the packet-switched communication apparatus;

obtaining a substitutive address from the selected address translator;

by using the obtained substitutive address, replacing a name query string generated from the specified address included in said name resolution request packet by a name query string generated from said substitutive address; and forwarding the name resolution request packet.

18. (Original) The communication method according to claim 17, further comprising:

receiving a name resolution request packet for a name corresponding to an IPv4 address;

replacing query data included in the received name resolution request packet by the obtained substitutive address;

transmitting a name resolution request packet with the replaced query data to a DNS server;

mapping a source IPv6 address of the received name resolution request to an ID of the name resolution request packet to transmit;

retaining a mapping between said source IPv6 address and said ID of the request packet;

receiving a reply packet for notification of the name corresponding to the IPv6 address;

selecting one of said address translators, based on the IPv6 address mapped to the ID of the reply packet; and

sending a request for a substitutive IPv4 address to the selected address translator.

19. (Original) The communication method according to claim 18, further comprising:

receiving a name resolution request packet for a name corresponding to an IPv6 address;

selecting one of said address translators, based on the IPv6 address corresponding to a string to be resolved to a name by the request included in the packet; and

sending a request for a substitutive IPv4 address to the selected address translator.

20. (Original) The communication method according to claim 19, further comprising:

receiving a reply packet for notification of the name corresponding to the IPv4 address;

selecting one of said address translators, based on the source IPv6 address of the packet; and

sending a request for a substitutive IPv6 address to the selected address translator.